



| | |
|----------------------|-----|
| Total creepage [mm] | 457 |
| Air-distance [mm] | 210 |
| Dry-flashover [kV] | 110 |
| Wet-flashover [kV] | 70 |
| Drywithstand [kV] | 70 |
| Wetwithstand [kV] | 50 |
| Impulse voltage [kV] | 125 |

| | | | | | |
|------------------|----------------------|------------------|-----------------|---------------|-----------------|
| U_N [kV] | 24 | PARALLEL ELEM. | 4 | CONNECTION | I |
| Q_N [kvar] | 506 | SERIES GROUPS | 12 | CASE MATERIAL | Stainless steel |
| C_N [μ F] | 2,8 (-/+10%) | WEIGHT [kg] | 70 | DIMENSIONS: | |
| f_N [Hz] | 50,0 | LIQUID CAP. [kg] | 16,9 | A [mm] | 175 |
| I_N [A] | 21,1 | STANDARD | IEC 60871/97 | B [mm] | 850 |
| I_{MAX} [A] | 80 | INT. FUSES | NO | C [mm] | 1164 |
| BIL [kV] | 50/125 | SIDE BRACKETS | YES | D [mm] | 100 |
| TEMP. CAT. | -40/C | BOTTOM BRACKETS | YES | DRAWN: | Křivánek |
| LIQUID | M-DBT (NON PCB) | TOP BOLTS | NO | CHECKED: | Novotný B. |
| DISCHARGE | 75 V/600 s (27 MOhm) | TYPE: | PUEFS 23-24/2,8 | DATE: | 3.4.2006 |
| DRAWING No.: | 4J7180A | | | | |



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
 Pod černým lesem 683
 564 22 Žamberk
 Czech Republic

tel.: +420 465 673 301
 fax.: +420 465 612 319
 e-mail: obchod@zez-silko.cz
 http:// www.zez-silko.cz