



Total creepage [mm]	457
Air-distance [mm]	210
Dry-flashover [kV]	110
Wet-flashover [kV]	70
Drywithstand [kV]	70
Wetwithstand [kV]	50
Impulse voltage [kV]	125

U_N [kV]	23	PARALLEL ELEM.	4	Total creepage [mm]	457
Q_N [kvar]	500	SERIES GROUPS	12	Air-distance [mm]	210
C_N [μ F]	3 (-4/+4%)	WEIGHT [kg]	71	Dry-flashover [kV]	110
f_N [Hz]	50,0	LIQUID CAP. [kg]	19,0	Wet-flashover [kV]	70
I_N [A]	21,7	STANDARD	IEC 60871/97	Drywithstand [kV]	70
BIL [kV]	50/125	INT. FUSES	NO	Wetwithstand [kV]	50
TEMP. CAT.	-40/C	SIDE BRACKETS	YES	Impulse voltage [kV]	125
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES	CONNECTION	I
DISCHARGE	75 V/600 s (27 MOhm)	TOP BOLTS	NO	CASE MATERIAL	Stainless steel
DRAWING No.:	4J7247A	TYPE:	PUEFS 23-23/3	DIMENSIONS:	
				A [mm]	175
				B [mm]	850
				C [mm]	1164
				D [mm]	100
				DRAWN:	Křivánek
				CHECKED:	Novotný B.
				DATE:	25.5.2006



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
Pod černým lesem 683
564 22 Žamberk
Czech Republic

tel.: +420 465 673 301
fax.: +420 465 612 319
e-mail: obchod@zez-silko.cz
http:// www.zez-silko.cz