



Total creepage [mm]	457
Air-distance [mm]	210
Dry-flashover [kV]	110
Wet-flashover [kV]	70
Drywithstand [kV]	70
Wetwithstand [kV]	50
Impulse voltage [kV]	125
CONNECTION	I
CASE MATERIAL	Stainless steel
DIMENSIONS:	
A [mm]	175
B [mm]	780
C [mm]	1094
D [mm]	100
DRAWN:	Křivánek
CHECKED:	Novotný B.
DATE:	10.10.2006

U_N [kV]	20	PARALLEL ELEM.	4
Q_N [kvar]	459,9	SERIES GROUPS	9
C_N [μ F]	3,66 (-3/+3%)	WEIGHT [kg]	64
f_N [Hz]	50,0	LIQUID CAP. [kg]	17,1
I_N [A]	23,0	STANDARD	IEC 60871/97
BIL [kV]	50/125	INT. FUSES	NO
TEMP. CAT.	-40/C	SIDE BRACKETS	YES
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES
DISCHARGE	75 V/600 s (24 MOhm)	TOP BOLTS	NO

DRAWING No.:	4J7398A	TYPE:	PUEFS 23-20/3,66
--------------	---------	-------	------------------



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
Pod černým lesem 683
564 22 Žamberk
Czech Republic

tel.: +420 465 673 301
fax.: +420 465 612 319
e-mail: obchod@zez-silko.cz
http:// www.zez-silko.cz