



Total creepage [mm]	457
Air-distance [mm]	210
Dry-flashover [kV]	110
Wet-flashover [kV]	70
Drywithstand [kV]	70
Wetwithstand [kV]	50
Impulse voltage [kV]	125

U_N [kV]	20	PARALLEL ELEM.	1	CONNECTION	I
Q_N [kvar]	37,7	SERIES GROUPS	9	CASE MATERIAL	Stainless steel
C_N [μ F]	0,3 (-5/+10%)	WEIGHT [kg]	21	DIMENSIONS:	
f_N [Hz]	50,0	LIQUID CAP. [kg]	8,0	A [mm]	145
I_N [A]	1,9	STANDARD	IEC 60871/97	B [mm]	250
BIL [kV]	50/125	INT. FUSES	NO	C [mm]	564
TEMP. CAT.	-40/C	SIDE BRACKETS	YES	D [mm]	100
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES	DRAWN:	Křivánek
DISCHARGE	75 V/600 s (36 MOhm)	TOP BOLTS	NO	CHECKED:	Novotný B.
DRAWING No.:	4J7450A	TYPE:	PUEFS 23-20/0,3	DATE:	7.11.2006



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
Pod černým lesem 683
564 22 Žamberk
Czech Republic

tel.: +420 465 673 301
fax.: +420 465 612 319
e-mail: obchod@zez-silko.cz
http:// www.zez-silko.cz