



Total creepage [mm]	457
Air-distance [mm]	210
Dry-flashover [kV]	110
Wet-flashover [kV]	70
Drywithstand [kV]	70
Wetwithstand [kV]	50
Impulse voltage [kV]	125

U_N [kV]	22	PARALLEL ELEM.	1	CONNECTION	I
Q_N [kvar]	45	SERIES GROUPS	12	CASE MATERIAL	Stainless steel
C_N [μ F]	0,3 (-5/+10%)	WEIGHT [kg]	22	DIMENSIONS:	
f_N [Hz]	50,0	LIQUID CAP. [kg]	7,5	A [mm]	145
I_N [A]	2,0	STANDARD	IEC 60871/97	B [mm]	250
BIL [kV]	50/125	INT. FUSES	NO	C [mm]	564
TEMP. CAT.	-40/C	SIDE BRACKETS	YES	D [mm]	100
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES	DRAWN: Stehlík	
DISCHARGE	-	TOP BOLTS	NO	CHECKED: Ing.Koryťák	
DRAWING No.:	4J7881A	TYPE:	PUEJS 23-22/0,3	DATE: 7.9.2007	



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
Pod černým lesem 683
564 22 Žamberk
Czech Republic

tel.: +420 465 673 301
fax.: +420 465 612 319
e-mail: obchod@zez-silko.cz
http:// www.zez-silko.cz