



Total creepage [mm]	457
Air-distance [mm]	210
Dry-flashover [kV]	110
Wet-flashover [kV]	70
Drywithstand [kV]	70
Wetwithstand [kV]	50
Impulse voltage [kV]	125

U_N [kV]	22	PARALLEL ELEM.	4	CONNECTION	I
Q_N [kvar]	-	SERIES GROUPS	12	CASE MATERIAL	Stainless steel
C_N [μ F]	4 (-3/+3%)	WEIGHT [kg]	79	DIMENSIONS:	
f_N [Hz]	50,0	LIQUID CAP. [kg]	19,6	A [mm]	200
I_N [A]	27,7	STANDARD	IEC 60871-1/05	B [mm]	870
BIL [kV]	LIVE CASE I	INT. FUSES	NO	C [mm]	1184
TEMP. CAT.	-40/C	SIDE BRACKETS	YES	D [mm]	100
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES	DRAWN:	Stehlík
DISCHARGE	75V/600s (20,4 MOhm)	TOP BOLTS	NO	CHECKED:	Ing.Koryťák
DRAWING No.:	4J7996A	TYPE:	PUFFS 23-22/4	DATE:	10.1.2008



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
Pod černým lesem 683
564 22 Žamberk
Czech Republic

tel.: +420 465 673 301
fax.: +420 465 612 319
e-mail: obchod@zez-silko.cz
http:// www.zez-silko.cz