



Total creepage [mm]	635
Air-distance [mm]	370
Dry-flashover [kV]	130
Wet-flashover [kV]	80
Drywithstand [kV]	80
Wetwithstand [kV]	70
Impulse voltage [kV]	170
<b>CONNECTION</b>	I
<b>CASE MATERIAL</b>	Stainless steel
<b>DIMENSIONS:</b>	
A [mm]	175
B [mm]	890
C [mm]	1245
D [mm]	100
<b>DRAWN:</b>	Stehlík
<b>CHECKED:</b>	Ing.Koryťák
<b>DATE:</b>	11.2.2008

$U_N$ [kV]	20	PARALLEL ELEM.	5
$Q_N$ [kvar]	(566)	SERIES GROUPS	10
$C_N$ [ $\mu$ F]	4,5 (-5/+10%)	WEIGHT [ kg]	75
$f_N$ [Hz]	50,0	LIQUID CAP. [kg]	17,5
$I_N$ [A]	28,3	STANDARD	IEC 60871-1/05
BIL [kV]	70/170	INT. FUSES	NO
TEMP. CAT.	-40/C	SIDE BRACKETS	YES
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES
DISCHARGE	75V/600s (20,4 MOhm)	TOP BOLTS	NO

DRAWING No.:	4J8054A	TYPE:	PUEFS 23-20/4,5
--------------	---------	-------	-----------------



ZEZ SILKO s.r.o.  
Žamberk  
CZECH REPUBLIC

ZEZ SILKO s.r.o.  
Pod černým lesem 683  
564 22 Žamberk  
Czech Republic

tel.: +420 465 673 301  
fax.: +420 465 612 319  
e-mail: [obchod@zez-silko.cz](mailto:obchod@zez-silko.cz)  
http:// [www.zez-silko.cz](http://www.zez-silko.cz)