



Total creepage [mm]	190
Air-distance [mm]	125
Dry-flashover [kV]	65
Wet-flashover [kV]	40
Drywithstand [kV]	38
Wetwithstand [kV]	28
Impulse voltage [kV]	75

U_N [kV]	6,3	PARALLEL ELEM.	8	Total creepage [mm]	190
Q_N [kvar]	450	GROUPS IN SERIES	2	Air-distance [mm]	125
C_N [μ F]	3x 36,1 (-5/+10%)	WEIGHT [kg]	60	Dry-flashover [kV]	65
f_N [Hz]	50,0	LIQUID CAP. [kg]	14,8	Wet-flashover [kV]	40
I_N [A]	41,2	STANDARD	IEC 60871/97	Drywithstand [kV]	38
BIL [kV]	20/60	INT. FUSES	YES	Wetwithstand [kV]	28
TEMP. CAT.	-40/C	SIDE BRACKETS	YES	Impulse voltage [kV]	75
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES	DIMENSIONS:	
DISCHARGE	75V/600s (3x2,2M Ω hm)	TOP BOLTS	NO	A [mm]	175
DRAWING No.:	4J5782A	TYPE:	CPEFS 23-6,3/450/WF	B [mm]	740
				C [mm]	958
				D [mm]	100
				DRAWN:	Křivánek
				CHECKED:	Novotny B.
				DATE:	16.6.2004



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
Pod černým lesem 683
564 22 Žamberk
Czech Republic

tel.: +420 465 673 301
fax.: +420 465 612 319
e-mail: obchod@zez-silko.cz
[http:// www.zez-silko.cz](http://www.zez-silko.cz)