



Total creepage [mm]	190
Air-distance [mm]	125
Dry-flashover [kV]	65
Wet-flashover [kV]	40
Drywithstand [kV]	38
Wetwithstand [kV]	28
Impulse voltage [kV]	75

U_N [kV]	6,3	PARALLEL ELEM.	10	U_N [kV]	6,3
Q_N [kvar]	600	GROUPS IN SERIES	2	CONNECTION	Y
C_N [μ F]	3x 48,1 (-5/+10%)	WEIGHT [kg]	77	CASE MATERIAL	Stainless steel
f_N [Hz]	50,0	LIQUID CAP. [kg]	18,2	DIMENSIONS:	
I_N [A]	55,0	STANDARD	IEC 60871/97	A [mm]	175
BIL [kV]	20/60	INT. FUSES	YES	B [mm]	960
TEMP. CAT.	-40/C	SIDE BRACKETS	YES	C [mm]	1180
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES	D [mm]	100
DISCHARGE	75V/600s (3x2,2M Ω)	TOP BOLTS	NO	DRAWN:	Křivánek
DRAWING No.:	4J5836A	TYPE:	CPEFS 23-6,3/600/WF	CHECKED:	Novotny B.
				DATE:	14.3.2005



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
Pod černým lesem 683
564 22 Žamberk
Czech Republic

tel.: +420 465 673 301
fax.: +420 465 612 319
e-mail: obchod@zez-silko.cz
[http:// www.zez-silko.cz](http://www.zez-silko.cz)