



Total creepage [mm]	190
Air-distance [mm]	125
Dry-flashover [kV]	65
Wet-flashover [kV]	40
Drywithstand [kV]	38
Wetwithstand [kV]	28
Impulse voltage [kV]	75

U_N [kV]	6,3	PARALLEL ELEM.	8	U_N [kV]	6,3
Q_N [kvar]	500	GROUPS IN SERIES	2	Q_N [kvar]	500
C_N [μ F]	3x 40,1 (-5/+10%)	WEIGHT [kg]	65	C_N [μ F]	3x 40,1 (-5/+10%)
f_N [Hz]	50,0	LIQUID CAP. [kg]	15,4	f_N [Hz]	50,0
I_N [A]	45,8	STANDARD	IEC 60871/97	I_N [A]	45,8
BIL [kV]	20/60	INT. FUSES	YES	BIL [kV]	20/60
TEMP. CAT.	-40/C	SIDE BRACKETS	YES	TEMP. CAT.	-40/C
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES	LIQUID	M-DBT (NON PCB)
DISCHARGE	75V/600s (3x2,2M Ω)	TOP BOLTS	NO	DISCHARGE	75V/600s (3x2,2M Ω)
DRAWING No.:	4J5899A	TYPE:	CPEFS 23-6,3/500/WF	DRAWN:	Křivánek
				CHECKED:	Novotny B.
				DATE:	12.7.2005



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
 Pod černým lesem 683
 564 22 Žamberk
 Czech Republic

tel.: +420 465 673 301
 fax.: +420 465 612 319
 e-mail: obchod@zez-silko.cz
[http:// www.zez-silko.cz](http://www.zez-silko.cz)