



Total creepage [mm]	190
Air-distance [mm]	125
Dry-flashover [kV]	65
Wet-flashover [kV]	40
Drywithstand [kV]	38
Wetwithstand [kV]	28
Impulse voltage [kV]	75

U_N [kV]	6,3	PARALLEL ELEM.	8	Total creepage [mm]		190
Q_N [kvar]	300	GROUPS IN SERIES	2	Air-distance [mm]		125
C_N [μ F]	3x 24,1 (-5/+10%)	WEIGHT [kg]	44	Dry-flashover [kV]		65
f_N [Hz]	50,0	LIQUID CAP. [kg]	11,9	Wet-flashover [kV]		40
I_N [A]	27,5	STANDARD	IEC 60871/97	Drywithstand [kV]		38
BIL [kV]	20/60	INT. FUSES	YES	Wetwithstand [kV]		28
TEMP. CAT.	-40/C	SIDE BRACKETS	YES	Impulse voltage [kV]		75
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES	DIMENSIONS:		
DISCHARGE	75V/600s (3x4,7M Ω)	TOP BOLTS	NO	A [mm]	145	
DRAWING No.:	4J5900A	TYPE:	CPEFS 23-6,3/300/WF	B [mm]	640	
				C [mm]	858	
				D [mm]	100	
				DRAWN:		Křivánek
				CHECKED:		Novotny B.
				DATE:		29.4.2004



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
Pod černým lesem 683
564 22 Žamberk
Czech Republic

tel.: +420 465 673 301
fax.: +420 465 612 319
e-mail: obchod@zez-silko.cz
http:// www.zez-silko.cz