



C2

a - změna umístění napouštěcího otvoru 16.4.2007 Křivánek

Total creepage [mm]	190
Air-distance [mm]	125
Dry-flashover [kV]	65
Wet-flashover [kV]	40
Drywithstand [kV]	38
Wetwithstand [kV]	28
Impulse voltage [kV]	75

<b>U<sub>N</sub> [kV]</b>	6,6	<b>DISCHARGE</b>	75V/600s(3x4,7MΩ)	<b>CONNECTION</b>	I
<b>Q<sub>N</sub> [kvar]</b>	250	<b>WEIGHT [ kg]</b>	39	<b>CASE MATERIAL</b>	Stainless steel
<b>C<sub>N</sub> [μF]</b>	3x 18,3 (-5/+10%)	<b>LIQUID CAP. [kg]</b>	10,7	<b>DIMENSIONS:</b>	
<b>f<sub>N</sub> [Hz]</b>	50	<b>STANDARD</b>	IEC 60871/97	<b>A [mm]</b>	145
<b>I<sub>N</sub> [A]</b>	21,9	<b>INT. FUSES</b>	NO	<b>B [mm]</b>	550
<b>BIL [kV]</b>	20/60	<b>SIDE BRACKETS</b>	YES	<b>C [mm]</b>	770
<b>TEMP. CAT.</b>	-40/C	<b>BOTTOM BRACKETS</b>	YES	<b>D [mm]</b>	100
<b>LIQUID</b>	M-DBT (NON PCB)	<b>TOP BOLTS</b>	NO	<b>DRAWN:</b>	Křivánek
<b>DRAWING No.:</b>	4J5935Aa	<b>TYPE:</b>	CPEFS 23-6,6/250	<b>CHECKED:</b>	Ing.Koryták
				<b>DATE:</b>	30.11.2004



ZEZ SILKO s.r.o.  
Žamberk  
CZECH REPUBLIC

ZEZ SILKO s.r.o.  
Pod černým lesem 683  
564 22 Žamberk  
Czech Republic

tel.: +420 465 673 301  
fax.: +420 465 612 319  
e-mail: [obchod@zez-silko.cz](mailto:obchod@zez-silko.cz)  
http:// [www.zez-silko.cz](http://www.zez-silko.cz)