



Total creepage [mm]	190
Air-distance [mm]	125
Dry-flashover [kV]	65
Wet-flashover [kV]	40
Drywithstand [kV]	38
Wetwithstand [kV]	28
Impulse voltage [kV]	75

U_N [kV]	10,5	PARALLEL ELEM.	6	CONNECTION	I
Q_N [kvar]	450	GROUPS IN SERIES	3	CASE MATERIAL	Stainless steel
C_N [μ F]	3x 13 (-5/+10%)	WEIGHT [kg]	59	DIMENSIONS:	
f_N [Hz]	50,0	LIQUID CAP. [kg]	15,2	A [mm]	175
I_N [A]	24,7	STANDARD	IEC 60871/97	B [mm]	740
BIL [kV]	28/75	INT. FUSES	YES	C [mm]	958
TEMP. CAT.	-40/C	SIDE BRACKETS	YES	D [mm]	100
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES	DRAWN: Křivánek	
DISCHARGE	75V/600s (3x6,8M Ω)	TOP BOLTS	NO	CHECKED: Novotný B.	
DRAWING No.:	4J5942A	TYPE:	CPEFS 23-10,5/450/WF	DATE: 21.5.2004	



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
Pod černým lesem 683
564 22 Žamberk
Czech Republic

tel.: +420 465 673 301
fax.: +420 465 612 319
e-mail: obchod@zez-silko.cz
http:// www.zez-silko.cz