



Total creepage [mm]	190
Air-distance [mm]	125
Dry-flashover [kV]	65
Wet-flashover [kV]	40
Drywithstand [kV]	38
Wetwithstand [kV]	28
Impulse voltage [kV]	75

U_N [kV]	6,6	PARALLEL ELEM.	8	U_N [kV]	6,6
Q_N [kvar]	650	GROUPS IN SERIES	2	Q_N [kvar]	650
C_N [μ F]	3x 47,5 (-5/+10%)	WEIGHT [kg]	81	C_N [μ F]	3x 47,5 (-5/+10%)
f_N [Hz]	50,0	LIQUID CAP. [kg]	20,6	f_N [Hz]	50,0
I_N [A]	56,9	STANDARD	IEC 60871/97	I_N [A]	56,9
BIL [kV]	20/60	INT. FUSES	YES	BIL [kV]	20/60
TEMP. CAT.	-40/C	SIDE BRACKETS	YES	TEMP. CAT.	-40/C
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES	LIQUID	M-DBT (NON PCB)
DISCHARGE	75V/600s (3x2,2M Ω)	TOP BOLTS	NO	DISCHARGE	75V/600s (3x2,2M Ω)

DRAWING No.:	4J5984A	TYPE:	CPEFS 23-6,6/650	DRAWN:	Křivánek
				CHECKED:	Novotny B.
				DATE:	23.6.2004

	ZEZ SILKO s.r.o. Žamberk CZECH REPUBLIC	ZEZ SILKO s.r.o. Pod černým lesem 683 564 22 Žamberk Czech Republic	tel.: +420 465 673 301 fax.: +420 465 612 319 e-mail: obchod@zez-silko.cz http:// www.zez-silko.cz
--	--	--	--