



Total creepage [mm]	190
Air-distance [mm]	125
Dry-flashover [kV]	65
Wet-flashover [kV]	40
Drywithstand [kV]	38
Wetwithstand [kV]	28
Impulse voltage [kV]	75

U_N [kV]	6,6	PARALLEL ELEM.	8	CONNECTION	Y
Q_N [kvar]	500	GROUPS IN SERIES	2	CASE MATERIAL	Stainless steel
C_N [μ F]	3x 36,5 (-5/+10%)	WEIGHT [kg]	65	DIMENSIONS:	
f_N [Hz]	50,0	LIQUID CAP. [kg]	16,2	A [mm]	175
I_N [A]	43,7	STANDARD	IEC 60871/97	B [mm]	810
BIL [kV]	20/60	INT. FUSES	YES	C [mm]	1028
TEMP. CAT.	-40/C	SIDE BRACKETS	YES	D [mm]	100
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES	DRAWN:	Křivánek
DISCHARGE	75V/600s (3x2,2M Ω)	TOP BOLTS	NO	CHECKED:	Novotny B.

DRAWING No.:	4J6252A	TYPE:	CPEFS 23-6,6/500/WF	DATE:	25.11.2004
--------------	---------	-------	---------------------	-------	------------



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
Pod černým lesem 683
564 22 Žamberk
Czech Republic

tel.: +420 465 673 301
fax.: +420 465 612 319
e-mail: obchod@zez-silko.cz
http:// www.zez-silko.cz