



a: filling hole moved from right side to left one 25.2.2008 Sth

Total creepage [mm]	190
Air-distance [mm]	125
Dry-flashover [kV]	65
Wet-flashover [kV]	40
Drywithstand [kV]	38
Wetwithstand [kV]	28
Impulse voltage [kV]	75

<b>U<sub>N</sub> [kV]</b>	7,2	<b>DISCHARGE</b>	75V/600s(3x12M0hm)	<b>CONNECTION</b>	I
<b>Q<sub>N</sub> [kvar]</b>	150	<b>WEIGHT [ kg]</b>	26	<b>CASE MATERIAL</b>	Stainless steel
<b>C<sub>N</sub> [µF]</b>	3x 9,2 (-5/+10%)	<b>LIQUID CAP. [kg]</b>	7,2	<b>DIMENSIONS:</b>	
<b>f<sub>N</sub> [Hz]</b>	50	<b>STANDARD</b>	IEC 60871/97	<b>A [mm]</b>	145
<b>I<sub>N</sub> [A]</b>	12,0	<b>INT. FUSES</b>	NO	<b>B [mm]</b>	350
<b>BIL [kV]</b>	28/75	<b>SIDE BRACKETS</b>	YES	<b>C [mm]</b>	570
<b>TEMP. CAT.</b>	-40/C	<b>BOTTOM BRACKETS</b>	YES	<b>D [mm]</b>	100
<b>LIQUID</b>	M-DBT (NON PCB)	<b>TOP BOLTS</b>	NO	<b>DRAWN:</b>	Křivánek
<b>DRAWING No.:</b>	4J6494Aa	<b>TYPE:</b>	CPEFS 23-7,2/150	<b>CHECKED:</b>	Novotny B.
				<b>DATE:</b>	11.2.2005



ZEZ SILKO s.r.o.  
Žamberk  
CZECH REPUBLIC

ZEZ SILKO s.r.o.  
Pod černým lesem 683  
564 22 Žamberk  
Czech Republic

tel.: +420 465 673 301  
fax.: +420 465 612 319  
e-mail: [obchod@zez-silko.cz](mailto:obchod@zez-silko.cz)  
http:// [www.zez-silko.cz](http://www.zez-silko.cz)