



Total creepage [mm]	190
Air-distance [mm]	125
Dry-flashover [kV]	65
Wet-flashover [kV]	40
Drywithstand [kV]	38
Wetwithstand [kV]	28
Impulse voltage [kV]	75

U_N [kV]	6,6	PARALLEL ELEM.	8	U_N [kV]	6,6
Q_N [kvar]	450	GROUPS IN SERIES	2	CONNECTION	Y
C_N [μ F]	3x 32,9 (-5/+10%)	WEIGHT [kg]	59	CASE MATERIAL	Stainless steel
f_N [Hz]	50,0	LIQUID CAP. [kg]	14,9	DIMENSIONS:	
I_N [A]	39,4	STANDARD	IEC 60871/97	A [mm]	175
BIL [kV]	20/60	INT. FUSES	YES	B [mm]	740
TEMP. CAT.	-40/C	SIDE BRACKETS	YES	C [mm]	960
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES	D [mm]	100
DISCHARGE	75V/600s (3x3,3M Ω)	TOP BOLTS	NO	DRAWN: Křivánek	
DRAWING No.: 4J6814A	TYPE: CPEFS 23-6,6/450/WF		CHECKED: Novotný B.		
			DATE: 31.8.2005		



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
 Pod černým lesem 683
 564 22 Žamberk
 Czech Republic

tel.: +420 465 673 301
 fax.: +420 465 612 319
 e-mail: obchod@zez-silko.cz
[http:// www.zez-silko.cz](http://www.zez-silko.cz)