



Total creepage [mm]	190
Air-distance [mm]	125
Dry-flashover [kV]	65
Wet-flashover [kV]	40
Drywithstand [kV]	38
Wetwithstand [kV]	28
Impulse voltage [kV]	75

U_N [kV]	7,2	DISCHARGE	75V/600s(3x4,7M Ω)	CONNECTION	Y
Q_N [kvar]	350	WEIGHT [kg]	48	CASE MATERIAL	Stainless steel
C_N [μ F]	3x 21,5 (-5/+10%)	LIQUID CAP. [kg]	12,1	DIMENSIONS:	
f_N [Hz]	50	STANDARD	IEC 60871/97	A [mm]	175
I_N [A]	28,1	INT. FUSES	NO	B [mm]	590
BIL [kV]	28/75	SIDE BRACKETS	YES	C [mm]	810
TEMP. CAT.	-40/C	BOTTOM BRACKETS	YES	D [mm]	100
LIQUID	M-DBT (NON PCB)	TOP BOLTS	NO	DRAWN:	Křivánek
DRAWING No.:	4J7158A	TYPE:	CPEFS 23-7,2/350	CHECKED:	Novotny B.
				DATE:	23.3.2006



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
 Pod černým lesem 683
 564 22 Žamberk
 Czech Republic

tel.: +420 465 673 301
 fax.: +420 465 612 319
 e-mail: obchod@zez-silko.cz
 http:// www.zez-silko.cz