



Zkušební napětí mezi svorkami (COM<--->64;64;32;16) 7,5 kV DC

Total creepage [mm]	50
Air-distance [mm]	40
Drywithstand [kV]	15
Wetwithstand [kV]	10
Impulse voltage [kV]	40

U_N [kV]	2,5	DISCHARGE	75 V / 10 min.	CONNECTION	I
Q_N [kvar]	345,6	WEIGHT [kg]	47	CASE MATERIAL	Stainless steel
C_N [mF] (+3/-3%)	64+64+32+16	LIQUID WEIGHT[kg]	12,6	DIMENSIONS:	
f_N [Hz]	50,0	STANDARD	TP 1/00	A [mm]	160
I_N [A]	138,2	INT. FUSES	NO	B [mm]	700
BIL [kV]	10/40	SIDE BRACKETS	YES	C [mm]	845
TEMP. CAT.	-40/C	BOTTOM BRACKETS	YES	D [mm]	100
LIQUID	JARYLEC	TOP BOLTS	NO	DRAWN:	Křivánek / Stehlík
DRAWING No.:	4J7373B	TYPE:	PUEFS 23-2,5/176/B	CHECKED:	Ing. Koryťák
				DATE:	18.2.2006



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
Pod černým lesem 683
564 22 Žamberk
Czech Republic

tel.: +420 465 673 301
fax.: +420 465 612 319
e-mail: obchod@zez-silko.cz
http:// www.zez-silko.cz