



Total creepage [mm]	635
Air-distance [mm]	370
Dry-flashover [kV]	130
Wet-flashover [kV]	80
Drywithstand [kV]	80
Wetwithstand [kV]	70
Impulse voltage [kV]	170

U_N [kV]	24	PARALLEL ELEM.	1	CONNECTION	I
U_{MAX} [kV]	25	SERIES GROUPS	12	CASE MATERIAL	Stainless steel
C_N [μ F]	0,3 (-5/+10%)	WEIGHT [kg]	23	DIMENSIONS:	
f_N [Hz]	50,0	LIQUID CAP. [kg]	7,6	A [mm]	145
I_N [A]	2,3	STANDARD	IEC 60871/97	B [mm]	250
BIL [kV]	70/170	INT. FUSES	NO	C [mm]	605
TEMP. CAT.	-40/C	SIDE BRACKETS	YES	D [mm]	100
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES	DRAWN: Křivánek	
DISCHARGE	-	TOP BOLTS	NO	CHECKED: Ing.Koryťák	
DRAWING No.:	4J7622A	TYPE:	PUEJS 23-24/0,3	DATE: 1.3.2007	



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
Pod černým lesem 683
564 22 Žamberk
Czech Republic

tel.: +420 465 673 301
fax.: +420 465 612 319
e-mail: obchod@zez-silko.cz
http:// www.zez-silko.cz