



Total creepage [mm]	457
Air-distance [mm]	210
Dry-flashover [kV]	110
Wet-flashover [kV]	70
Drywithstand [kV]	70
Wetwithstand [kV]	50
Impulse voltage [kV]	125
<b>CONNECTION</b>	I
<b>CASE MATERIAL</b>	Stainless steel
<b>DIMENSIONS:</b>	
A [mm]	145
B [mm]	250
C [mm]	564
D [mm]	100
<b>DRAWN:</b>	Stehlík
<b>CHECKED:</b>	Ing.Koryťák
<b>DATE:</b>	7.2.2008

$U_N$ [kV]	15	PARALLEL ELEM.	1
$Q_N$ [kvar]	17,7	SERIES GROUPS	9
$C_N$ [ $\mu$ F]	0,25 (-5/+10%)	WEIGHT [ kg]	21
$f_N$ [Hz]	50,0	LIQUID CAP. [kg]	8,6
$I_N$ [A]	1,2	STANDARD	IEC 60871-1/05
BIL [kV]	LIVE CASE I	INT. FUSES	NO
TEMP. CAT.	-40/C	SIDE BRACKETS	YES
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES
DISCHARGE	--	TOP BOLTS	NO
<b>DRAWING No.:</b>	4J7642Ab	<b>TYPE:</b>	PUFJS 23-15/0,25



ZEZ SILKO s.r.o.  
Žamberk  
CZECH REPUBLIC

ZEZ SILKO s.r.o.  
Pod černým lesem 683  
564 22 Žamberk  
Czech Republic

tel.: +420 465 673 301  
fax.: +420 465 612 319  
e-mail: [obchod@zez-silko.cz](mailto:obchod@zez-silko.cz)  
http:// [www.zez-silko.cz](http://www.zez-silko.cz)