



Total creepage [mm]	317
Air-distance [mm]	165
Dry-flashover [kV]	85
Wet-flashover [kV]	50
Drywithstand [kV]	50
Wetwithstand [kV]	38
Impulse voltage [kV]	95
CONNECTION	I
CASE MATERIAL	Stainless steel
DIMENSIONS:	
A [mm]	145
B [mm]	250
C [mm]	522
D [mm]	100
DRAWN:	Křivánek
CHECKED:	Ing.Koryťák
DATE:	25.4.2007

U_N [kV]	15	PARALLEL ELEM.	1
Q_N [kvar]	35,34	SERIES GROUPS	9
C_N [μF]	0,5 (-5/+10%)	WEIGHT [kg]	20
f_N [Hz]	50,0	LIQUID CAP. [kg]	7,7
I_N [A]	2,4	STANDARD	IEC 60871-1/05
BIL [kV]	38/95	INT. FUSES	NO
TEMP. CAT.	-40/C	SIDE BRACKETS	YES
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES
DISCHARGE	75 V/600 s (60 MOhm)	TOP BOLTS	NO

DRAWING No.:	4J7714A	TYPE:	PUEFS 23-15/0,5
--------------	---------	-------	-----------------



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
Pod černým lesem 683
564 22 Žamberk
Czech Republic

tel.: +420 465 673 301
fax.: +420 465 612 319
e-mail: obchod@zez-silko.cz
http:// www.zez-silko.cz