



Total creepage [mm]	50
Air-distance [mm]	40
Dry-flashover [kV]	20
Wet-flashover [kV]	12
Drywithstand [kV]	15
Wetwithstand [kV]	10
Impulse voltage [kV]	40

U_N [kV]	1	DISCHARGE	75 V / 10 min.	CONNECTION	I
C_N [μ F]	70,0	WEIGHT [kg]	14	CASE MATERIAL	Stainless steel
f_N [Hz]	50,0	LIQUID CAP. [kg]	6	DIMENSIONS:	
I_N [A]	22,0	STANDARD	IEC 60871/97	A [mm]	145
I_{MAX} [A]	70	INT. FUSES	NO	B [mm]	170
BIL [kV]	10/40	SIDE BRACKETS	YES	C [mm]	725
TEMP. CAT.	-40/C	BOTTOM BRACKETS	YES	D [mm]	100
LIQUID	JARYLEC	TOP BOLTS	NO	DRAWN: Křivánek	
DRAWING No.:	4J7793A	TYPE:	PUEFS 23-1/70	CHECKED:	Ing.Koryťák
				DATE:	25.6.2007



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
Pod černým lesem 683
564 22 Žamberk
Czech Republic

tel.: +420 465 673 301
fax.: +420 465 612 319
e-mail: obchod@zez-silko.cz
http:// www.zez-silko.cz