



Total creepage [mm]	457
Air-distance [mm]	210
Dry-flashover [kV]	110
Wet-flashover [kV]	70
Drywithstand [kV]	70
Wetwithstand [kV]	50
Impulse voltage [kV]	125
CONNECTION	I
CASE MATERIAL	Stainless steel
<b>DIMENSIONS:</b>	
A [mm]	175
B [mm]	570
C [mm]	884
D [mm]	100
DRAWN:	Křivánek
CHECKED:	Ing. Koryťák
DATE:	11.7.2007

$U_N$ [kV]	20	PARALLEL ELEM.	3
$Q_N$ [kvar]	314,159	SERIES GROUPS	9
$C_N$ [ $\mu$ F]	2,5 (-3/+3%)	WEIGHT [kg]	48
$f_N$ [Hz]	50,0	LIQUID CAP. [kg]	12,9
$I_N$ [A]	15,7	STANDARD	IEC 60871-1/05
BIL [kV]	50/125	INT. FUSES	NO
TEMP. CAT.	-40/C	SIDE BRACKETS	YES
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES
DISCHARGE	75 V/600 s (24 MOhm)	TOP BOLTS	NO

DRAWING No.:	4J7814A	TYPE:	PUEFS 23-20/2,5
--------------	---------	-------	-----------------



ZEZ SILKO s.r.o.  
Žamberk  
CZECH REPUBLIC

ZEZ SILKO s.r.o.  
Pod černým lesem 683  
564 22 Žamberk  
Czech Republic

tel.: +420 465 673 301  
fax.: +420 465 612 319  
e-mail: [obchod@zez-silko.cz](mailto:obchod@zez-silko.cz)  
http:// [www.zez-silko.cz](http://www.zez-silko.cz)