



Total creepage [mm]	260
Air-distance [mm]	130
Dry-flashover [kV]	65
Wet-flashover [kV]	40
Drywithstand [kV]	38
Wetwithstand [kV]	28
Impulse voltage [kV]	75

U_N [kV]	7,2	DISCHARGE	75V/600s(3x4,7MOhm)	CONNECTION	Y
Q_N [kvar]	300	WEIGHT [kg]	45	CASE MATERIAL	Stainless steel
C_N [μ F]	3x 18,4 (-5/+10%)	LIQUID CAP. [kg]	12,9	DIMENSIONS:	
f_N [Hz]	50	STANDARD	IEC 60871-1/05	A [mm]	145
I_N [A]	24,1	INT. FUSES	NO	B [mm]	640
BIL [kV]	28/75	SIDE BRACKETS	YES	C [mm]	840
TEMP. CAT.	-40/C	BOTTOM BRACKETS	YES	D [mm]	100
LIQUID	M-DBT (NON PCB)	TOP BOLTS	NO	DRAWN:	Stehlík
DRAWING No.:	4J7905A	TYPE:	CPEFS 23-7,2/300	CHECKED:	Ing. Koryták
				DATE:	5.10.2007



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
Pod černým lesem 683
564 22 Žamberk
Czech Republic

tel.: +420 465 673 301
fax.: +420 465 612 319
e-mail: obchod@zez-silko.cz
http:// www.zez-silko.cz