



Total creepage [mm]	457
Air-distance [mm]	210
Dry-flashover [kV]	110
Wet-flashover [kV]	70
Drywithstand [kV]	70
Wetwithstand [kV]	50
Impulse voltage [kV]	125

$U_N$ [kV]	17,5	PARALLEL ELEM.	1	CONNECTION	I
$Q_N$ [kvar]	24,1	SERIES GROUPS	9	CASE MATERIAL	Stainless steel
$C_N$ [ $\mu$ F]	0,25 (-5/+10%)	WEIGHT [ kg]	15	DIMENSIONS:	
$f_N$ [Hz]	50,0	LIQUID CAP. [kg]	5,3	A [mm]	145
$I_N$ [A]	1,4	STANDARD	IEC 60871-1/05	B [mm]	170
BIL [kV]	Live case	INT. FUSES	NO	C [mm]	484
TEMP. CAT.	-40/C	SIDE BRACKETS	YES	D [mm]	100
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES	DRAWN:	Stehlík
DISCHARGE	75 V/600 s (60 MOhm)	TOP BOLTS	NO	CHECKED:	Ing.Koryťák
DRAWING No.:	4J7961A	TYPE:	PUFFS 23-17,5/0,25	DATE:	23.11.2007



ZEZ SILKO s.r.o.  
Žamberk  
CZECH REPUBLIC

ZEZ SILKO s.r.o.  
Pod černým lesem 683  
564 22 Žamberk  
Czech Republic

tel.: +420 465 673 301  
fax.: +420 465 612 319  
e-mail: [obchod@zez-silko.cz](mailto:obchod@zez-silko.cz)  
http:// [www.zez-silko.cz](http://www.zez-silko.cz)