



Total creepage [mm]	50
Air-distance [mm]	40
Dry-flashover [kV]	20
Wet-flashover [kV]	12
Drywithstand [kV]	15
Wetwithstand [kV]	10
Impulse voltage [kV]	40
<b>CONNECTION</b>	I
<b>CASE MATERIAL</b>	Stainless steel
<b>DIMENSIONS:</b>	
A [mm]	200
B [mm]	1030
C [mm]	1055
D [mm]	100
<b>DRAWN:</b>	Křivánek
<b>CHECKED:</b>	Ing. Novotný
<b>DATE:</b>	9.11.2005

$U_N$ [kV]	2,4	PARALLEL ELEM.	24+24
$Q_N$ [kvar]	361,9+361,9	GROUPS IN SERIES	1
$C_N$ [μF]	200+200	WEIGHT [ kg]	100
$f_N$ [Hz]	50,0	LIQUID CAP. [kg]	21,8
$I_N$ [A]	301,6	STANDARD	IEC 60871/97
BIL [kV]	10/40	INT. FUSES	NO
TEMP. CAT.	-40/C	SIDE BRACKETS	YES
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES
DISCHARGE	-	TOP BOLTS	NO
DRAWING No.:	4J 6958 A	TYPE:	PUEFS 23-2,4/400



ZEZ SILKO s.r.o.  
Žamberk  
CZECH REPUBLIC

ZEZ SILKO s.r.o.  
Pod černým lesem 683  
564 22 Žamberk  
Czech Republic

tel.: +420 465 673 301  
fax.: +420 465 612 319  
e-mail: [obchod@zez-silko.cz](mailto:obchod@zez-silko.cz)  
http:// [www.zez-silko.cz](http://www.zez-silko.cz)