



Total creepage [mm]	457
Air-distance [mm]	210
Dry-flashover [kV]	110
Wet-flashover [kV]	70
Drywithstand [kV]	70
Wetwithstand [kV]	50
Impulse voltage [kV]	125

U_N [kV]	23	PARALLEL ELEM.	3	CONNECTION		I
Q_N [kvar]	465	SERIES GROUPS	12	CASE MATERIAL		Stainless steel
C_N [μ F]	2,8 (-4/+4%)	WEIGHT [kg]	65	DIMENSIONS:		
f_N [Hz]	50,0	LIQUID CAP. [kg]	16,7	A [mm]	175	
I_N [A]	20,2	STANDARD	IEC 60871/97	B [mm]	780	
BIL [kV]	50/125	INT. FUSES	NO	C [mm]	1094	
TEMP. CAT.	-40/C	SIDE BRACKETS	YES	D [mm]	100	
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES	DRAWN: Křivánek		
DISCHARGE	75 V/600 s (27 MOhm)	TOP BOLTS	NO	CHECKED: Novotný B.		
DRAWING No.: 4J7342A	TYPE: PUEFS 23-23/2,8		DATE: 24.8.2006			



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
Pod černým lesem 683
564 22 Žamberk
Czech Republic

tel.: +420 465 673 301
fax.: +420 465 612 319
e-mail: obchod@zez-silko.cz
http:// www.zez-silko.cz