



Total creepage [mm]	190
Air-distance [mm]	125
Dry-flashover [kV]	65
Wet-flashover [kV]	40
Drywithstand [kV]	38
Wetwithstand [kV]	28
Impulse voltage [kV]	75

U_N [kV]	12	PARALLEL ELEM.	1	U_N [kV]	12
Q_N [kvar]	11,3	SERIES GROUPS	9	CONNECTION	I
C_N [μ F]	0,25 (-5/+10%)	WEIGHT [kg]	14	CASE MATERIAL	Stainless steel
f_N [Hz]	50,0	LIQUID CAP. [kg]	5,1	DIMENSIONS:	
I_N [A]	0,9	STANDARD	IEC 60871/97	A [mm]	145
BIL [kV]	28/75	INT. FUSES	NO	B [mm]	170
TEMP. CAT.	-40/C	SIDE BRACKETS	YES	C [mm]	390
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES	D [mm]	100
DISCHARGE	75 V/600 s (24 MOhm)	TOP BOLTS	NO		

DRAWING No.:	4J7353A	TYPE:	PUEFS 23-12/0,25	DRAWN:	Křivánek
				CHECKED:	Novotný B.
				DATE:	30.8.2006

	ZEZ SILKO s.r.o. Žamberk CZECH REPUBLIC	ZEZ SILKO s.r.o. Pod černým lesem 683 564 22 Žamberk Czech Republic	tel.: +420 465 673 301 fax.: +420 465 612 319 e-mail: obchod@zez-silko.cz http:// www.zez-silko.cz
--	--	--	--