



Total creepage [mm]	457
Air-distance [mm]	210
Dry-flashover [kV]	110
Wet-flashover [kV]	70
Drywithstand [kV]	70
Wetwithstand [kV]	50
Impulse voltage [kV]	125
CONNECTION	I
CASE MATERIAL	Stainless steel
DIMENSIONS:	
A [mm]	200
B [mm]	990
C [mm]	1304
D [mm]	100
DRAWN:	Křivánek
CHECKED:	Ing.Koryťák
DATE:	19.2.2007

U_N [kV]	20	PARALLEL ELEM.	5
C_N [µF]	6 (-4/+4%)	SERIES GROUPS	9
f_N [Hz]	50,0	WEIGHT [kg]	89
I_N [A]	37,7	LIQUID CAP. [kg]	20,2
I_{MAX} [A]	90	STANDARD	IEC 60871/97
BIL [kV]	50/125	INT. FUSES	NO
TEMP. CAT.	-40/C	SIDE BRACKETS	YES
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES
DISCHARGE	75 V/600 s (12 MOhm)	TOP BOLTS	NO

DRAWING No.:	4J7635A	TYPE:	PUEFS 23-20/6
--------------	---------	-------	---------------



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
Pod černým lesem 683
564 22 Žamberk
Czech Republic

tel.: +420 465 673 301
fax.: +420 465 612 319
e-mail: obchod@zez-silko.cz
http:// www.zez-silko.cz