



Total creepage [mm]	50
Air-distance [mm]	40
Dry-flashover [kV]	20
Wet-flashover [kV]	12
Drywithstand [kV]	15
Wetwithstand [kV]	10
Impulse voltage [kV]	40

$U_N$ [kV]	1	DISCHARGE	75 V / 10 min.	CONNECTION	I
$C_N$ [ $\mu$ F]	3x50	WEIGHT [kg]	19	CASE MATERIAL	Stainless steel
$f_N$ [Hz]	50,0	LIQUID CAP. [kg]	7	DIMENSIONS:	
$I_N$ [A]	3x15,7	STANDARD	IEC 60871/97	A [mm]	145
$I_{MAX}$ [A]	120 A / 420 Hz	INT. FUSES	NO	B [mm]	250
BIL [kV]	10/40	SIDE BRACKETS	YES	C [mm]	375
TEMP. CAT.	-40/C	BOTTOM BRACKETS	YES	D [mm]	100
LIQUID	JARYLEC	TOP BOLTS	NO	DRAWN: Křivánek	
DRAWING No.:	4J7674A	TYPE:	PUEFS 23-1/3x50	CHECKED:	Ing.Koryťák
			DATE: 20.3.2007		



ZEZ SILKO s.r.o.  
Žamberk  
CZECH REPUBLIC

ZEZ SILKO s.r.o.  
Pod černým lesem 683  
564 22 Žamberk  
Czech Republic

tel.: +420 465 673 301  
fax.: +420 465 612 319  
e-mail: [obchod@zez-silko.cz](mailto:obchod@zez-silko.cz)  
http:// [www.zez-silko.cz](http://www.zez-silko.cz)