



Proletovaná čela svitků - soldering front of elements
 Venkovní provedení - outdoor service

Total creepage [mm]	457
Air-distance [mm]	210
Dry-flashover [kV]	110
Wet-flashover [kV]	70
Drywithstand [kV]	70
Wetwithstand [kV]	50
Impulse voltage [kV]	125
CONNECTION	I
CASE MATERIAL	Stainless steel
DIMENSIONS:	
A [mm]	175
B [mm]	710
C [mm]	1024
D [mm]	100
DRAWN:	Křivánek
CHECKED:	Ing.Koryťák
DATE:	25.5.2007

U_N [kV]	17,3	PARALLEL ELEM.	5
C_N [μ F]	4,8 (-3/+3%)	SERIES GROUPS	8
f_N [Hz]	50,0	WEIGHT [kg]	59
I_N [A]	13,5	LIQUID CAP. [kg]	15,1
IMAX [A]	70 A/216,6 Hz	STANDARD	IEC 60871-1/05
BIL [kV]	Live case I	INT. FUSES	NO
TEMP. CAT.	-30/+45 °C	SIDE BRACKETS	YES
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES
DISCHARGE	75 V/600 s (18 MOhm)	TOP BOLTS	NO

DRAWING No.:	4J7751A	TYPE:	PUFFS 23-17,3/4,8
--------------	---------	-------	-------------------



ZEZ SILKO s.r.o.
 Žamberk
 CZECH REPUBLIC

ZEZ SILKO s.r.o.
 Pod černým lesem 683
 564 22 Žamberk
 Czech Republic

tel.: +420 465 673 301
 fax.: +420 465 612 319
 e-mail: obchod@zez-silko.cz
 http:// www.zez-silko.cz