



Total creepage [mm]	190
Air-distance [mm]	125
Dry-flashover [kV]	65
Wet-flashover [kV]	40
Drywithstand [kV]	38
Wetwithstand [kV]	28
Impulse voltage [kV]	75
<b>CONNECTION</b>	I
<b>CASE MATERIAL</b>	Stainless steel
<b>DIMENSIONS:</b>	
A [mm]	145
B [mm]	170
C [mm]	390
D [mm]	100
<b>DRAWN:</b>	Stehlík
<b>CHECKED:</b>	Ing.Koryťák
<b>DATE:</b>	5.9.2007

$U_N$ [kV]	10,5	PARALLEL ELEM.	1
$Q_N$ [kvar]	10,4	SERIES GROUPS	7
$C_N$ [ $\mu$ F]	0,3 (-5/+5%)	WEIGHT [kg]	14
$f_N$ [Hz]	50,0	LIQUID CAP. [kg]	5,0
$I_N$ [A]	1,0	STANDARD	IEC 60871/97
BIL [kV]	LIVE CASE	INT. FUSES	NO
TEMP. CAT.	-40/C	SIDE BRACKETS	YES
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES
DISCHARGE	75 V/600 s (30 MOhm)	TOP BOLTS	NO

DRAWING No.:	4J7874A	TYPE:	PUFFS 23-10,5/0,3
--------------	---------	-------	-------------------



ZEZ SILKO s.r.o.  
Žamberk  
CZECH REPUBLIC

ZEZ SILKO s.r.o.  
Pod černým lesem 683  
564 22 Žamberk  
Czech Republic

tel.: +420 465 673 301  
fax.: +420 465 612 319  
e-mail: [obchod@zez-silko.cz](mailto:obchod@zez-silko.cz)  
http:// [www.zez-silko.cz](http://www.zez-silko.cz)