



Total creepage [mm]	744
Air-distance [mm]	410
Dry-flashover [kV]	150
Wet-flashover [kV]	110
Drywithstand [kV]	95
Wetwithstand [kV]	95
Impulse voltage [kV]	250
CONNECTION	I
CASE MATERIAL	Stainless steel
DIMENSIONS:	
A [mm]	145
B [mm]	420
C [mm]	775
D [mm]	100
DRAWN:	Stehlík
CHECKED:	Ing.Koryťák
DATE:	8.10.2007

U_N [kV]	15,25	PARALLEL ELEM.	2
Q_N [kvar]	146,1	SERIES GROUPS	8
C_N [μ F]	2 (-0/+8%)	WEIGHT [kg]	31
f_N [Hz]	50,0	LIQUID CAP. [kg]	10,8
I_N [A]	9,6	STANDARD	IEC 60871-1/05
BIL [kV]	LIVE CASE I	INT. FUSES	NO
TEMP. CAT.	-40/C	SIDE BRACKETS	YES
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES
DISCHARGE	75 V/600 s (27 MOhm)	TOP BOLTS	NO

DRAWING No.:	4J7913A	TYPE:	PUFFS 23-15,25/2
--------------	---------	-------	------------------



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
Pod černým lesem 683
564 22 Žamberk
Czech Republic

tel.: +420 465 673 301
fax.: +420 465 612 319
e-mail: obchod@zez-silko.cz
http:// www.zez-silko.cz