



Total creepage [mm]	317
Air-distance [mm]	165
Dry-flashover [kV]	85
Wet-flashover [kV]	50
Drywithstand [kV]	50
Wetwithstand [kV]	38
Impulse voltage [kV]	95

U_N [kV]	13,8	PARALLEL ELEM.	1	CONNECTION	I
Q_N [kvar]	(14,95)	SERIES GROUPS	9	CASE MATERIAL	Stainless steel
C_N [μ F]	0,25 (-5/+10%)	WEIGHT [kg]	15	DIMENSIONS:	
f_N [Hz]	50,0	LIQUID CAP. [kg]	5,4	A [mm]	145
I_N [A]	1,1	STANDARD	IEC 60871-1/05	B [mm]	170
BIL [kV]	Live Case!	INT. FUSES	NO	C [mm]	442
TEMP. CAT.	-40/C	SIDE BRACKETS	YES	D [mm]	100
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES	DRAWN:	Stehlík
DISCHARGE	75 V/600 s (30 MOhm)	TOP BOLTS	NO	CHECKED:	Ing.Koryťák
DRAWING No.:	4J8130A	TYPE:	PUFFS 23-13,8/0,25	DATE:	11.4.2008



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
Pod černým lesem 683
564 22 Žamberk
Czech Republic

tel.: +420 465 673 301
fax.: +420 465 612 319
e-mail: obchod@zez-silko.cz
http:// www.zez-silko.cz