



Total creepage [mm]	260
Air-distance [mm]	130
Dry-flashover [kV]	65
Wet-flashover [kV]	40
Drywithstand [kV]	38
Wetwithstand [kV]	28
Impulse voltage [kV]	75

$U_{N/TIT} U_{N/TIC}$ [kV]	12 6,93	DISCHARGE	75V/600s(3x30MΩ)	CONNECTION	YN
Q_N [kvar]	(22,6)	WEIGHT [kg]	43	CASE MATERIAL	Stainless steel
C_N [μF]	3x 0,5 (-5/+10%)	LIQUID CAP. [kg]	26,1	DIMENSIONS:	
f_N [Hz]	50	STANDARD	IEC 60871-1/05	A [mm]	145
I_N [A]	1,1	INT. FUSES	NO	B [mm]	640
BIL [kV]	LIVE CASE !	SIDE BRACKETS	YES	C [mm]	840
TEMP. CAT.	-40/C	BOTTOM BRACKETS	YES	D [mm]	100
LIQUID	M-DBT (NON PCB)	R_S [Ω]	3x 30	DRAWN: Stehlik	
DRAWING No.: 4J9329A		TYPE: PFFS 23-12/3x0,5/3x30Ω		CHECKED: Ing.Koryt'ák	
				DATE: 24.9.2010	



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
 Pod černým lesem 683
 564 22 Žamberk
 Czech Republic

tel.: +420 465 673 111
 fax.: +420 465 612 319
 e-mail: zez@zez-silko.cz
 http:// www.zez-silko.cz