



Total creepage [mm]	190
Air-distance [mm]	125
Dry-flashover [kV]	65
Wet-flashover [kV]	40
Drywithstand [kV]	38
Wetwithstand [kV]	28
Impulse voltage [kV]	75
<b>CONNECTION</b>	I
<b>CASE MATERIAL</b>	Stainless steel
<b>DIMENSIONS:</b>	
A [mm]	145
B [mm]	170
C [mm]	390
D [mm]	100
<b>DRAWN:</b>	Stehlík J.
<b>CHECKED:</b>	Prokopec M.
<b>DATE:</b>	11.4.2014

$U_N$ [kV]	12	PARALLEL ELEM.	1
$Q_N$ [kvar]	( 11,3   13,6 )	SERIES GROUPS	9
$C_N$ [µF]	0,25 (-5/+10%)	WEIGHT [ kg]	13
$f_N$ [Hz]	50   60	LIQUID CAP. [kg]	5,4
$I_N$ [A]	0,9   1,1	STANDARD	IEC 60871-1/05
BIL [kV]	LIVE CASE!	INT. FUSES	NO
TEMP. CAT.	-40/C	SIDE BRACKETS	YES
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES
DISCHARGE	75 V/600 s (120 MΩ)		

DRAWING No.:	4K0726A	TYPE:	PUFFS 23-12/0,25
--------------	---------	-------	------------------



ZEZ SILKO s.r.o.  
Žamberk  
CZECH REPUBLIC

ZEZ SILKO s.r.o.  
Pod černým lesem 683  
564 01 Žamberk  
Czech Republic

tel.: +420 465 673 111  
fax.: +420 465 612 319  
e-mail: [zez@zez-silko.cz](mailto:zez@zez-silko.cz)  
http:// [www.zez-silko.cz](http://www.zez-silko.cz)