



Total creepage [mm]	190
Air-distance [mm]	125
Dry-flashover [kV]	65
Wet-flashover [kV]	40
Drywithstand [kV]	38
Wetwithstand [kV]	28
Impulse voltage [kV]	75

U_N [kV]	12	PARALLEL ELEM.	1	CONNECTION	I
Q_N [kvar]	(18,1 21,7)	SERIES GROUPS	8	CASE MATERIAL	Stainless steel
C_N [μ F]	0,40 (-5/+10%)	WEIGHT [kg]	16	DIMENSIONS:	
f_N [Hz]	50 60	LIQUID CAP. [kg]	6,7	A [mm]	145
I_N [A]	1,5 1,8	STANDARD	IEC 60871-1/05	B [mm]	210
BIL [kV]	LIVE CASE!	INT. FUSES	NO	C [mm]	430
TEMP. CAT.	-40/C	SIDE BRACKETS	YES	D [mm]	100
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES	DRAWN: Stehlík J.	
DISCHARGE	75 V/600 s (90 M Ω)			CHECKED: Prokopec M.	

DRAWING No.:	4K0728A	TYPE:	PUFFS 23-12/0,4	DATE:	11.4.2014
--------------	---------	-------	-----------------	-------	-----------



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
Pod černým lesem 683
564 01 Žamberk
Czech Republic

tel.: +420 465 673 111
fax.: +420 465 612 319
e-mail: zez@zez-silko.cz
http:// www.zez-silko.cz