



Total creepage [mm]	317
Air-distance [mm]	165
Dry-flashover [kV]	85
Wet-flashover [kV]	50
Drywithstand [kV]	50
Wetwithstand [kV]	38
Impulse voltage [kV]	95

$U_N$ [kV]	17,5	PARALLEL ELEM.	1	CONNECTION	I
$Q_N$ [kvar]	( 48,1   57,8 )	SERIES GROUPS	10	CASE MATERIAL	Stainless steel
$C_N$ [ $\mu$ F]	0,50 (-5/+10%)	WEIGHT [ kg]	22	DIMENSIONS:	
$f_N$ [Hz]	50   60	LIQUID CAP. [kg]	8,0	A [mm]	145
$I_N$ [A]	2,7   3,3	STANDARD	IEC 60871-1/05	B [mm]	300
BIL [kV]	LIVE CASE!	INT. FUSES	NO	C [mm]	572
TEMP. CAT.	-40/C	SIDE BRACKETS	YES	D [mm]	100
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES		
DISCHARGE	75 V/600 s (60 M $\Omega$ )				

DRAWING No.:	4K0738A	TYPE:	PUFFS 23-17,5/0,5	DRAWN:	Stehlík J.
				CHECKED:	Prokopec M.
				DATE:	11.4.2014



ZEZ SILKO s.r.o.  
Žamberk  
CZECH REPUBLIC

ZEZ SILKO s.r.o.  
Pod černým lesem 683  
564 01 Žamberk  
Czech Republic

tel.: +420 465 673 111  
fax.: +420 465 612 319  
e-mail: [zez@zez-silko.cz](mailto:zez@zez-silko.cz)  
http:// [www.zez-silko.cz](http://www.zez-silko.cz)