



Total creepage [mm]	435
Air-distance [mm]	210
Dry-flashover [kV]	110
Wet-flashover [kV]	70
Drywithstand [kV]	70
Wetwithstand [kV]	50
Impulse voltage [kV]	125
CONNECTION	I
CASE MATERIAL	Stainless steel
<b>DIMENSIONS:</b>	
A [mm]	145
B [mm]	210
C [mm]	524
D [mm]	100
DRAWN:	Stehlík J.
CHECKED:	Prokopec M.
DATE:	14.4.2014

$U_N$ [kV]	24	PARALLEL ELEM.	1
$Q_N$ [kvar]	( 18,1   21,8 )	SERIES GROUPS	14
$C_N$ [ $\mu$ F]	0,10 (-5/+10%)	WEIGHT [ kg]	18
$f_N$ [Hz]	50   60	LIQUID CAP. [kg]	6,9
$I_N$ [A]	0,8   0,9	STANDARD	IEC 60871-1/05
BIL [kV]	LIVE CASE !	INT. FUSES	NO
TEMP. CAT.	-40/C	SIDE BRACKETS	YES
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES
DISCHARGE	75 V/600 s (120 M $\Omega$ )		

DRAWING No.:	4K0741A	TYPE:	PUFFS 23-24/0,1
--------------	---------	-------	-----------------



ZEZ SILKO s.r.o.  
Žamberk  
CZECH REPUBLIC

ZEZ SILKO s.r.o.  
Pod černým lesem 683  
564 01 Žamberk  
Czech Republic

tel.: +420 465 673 111  
fax.: +420 465 612 319  
e-mail: [zez@zez-silko.cz](mailto:zez@zez-silko.cz)  
http:// [www.zez-silko.cz](http://www.zez-silko.cz)