



Total creepage [mm]	435
Air-distance [mm]	210
Dry-flashover [kV]	110
Wet-flashover [kV]	70
Drywithstand [kV]	70
Wetwithstand [kV]	50
Impulse voltage [kV]	125
CONNECTION	I
CASE MATERIAL	Stainless steel
DIMENSIONS:	
A [mm]	145
B [mm]	300
C [mm]	614
D [mm]	100
DRAWN:	Stehlík J.
CHECKED:	Prokopec M.
DATE:	14.4.2014

U_N [kV]	24	PARALLEL ELEM.	1
Q_N [kvar]	(45,3 54,3)	SERIES GROUPS	14
C_N [µF]	0,25 (-5/+10%)	WEIGHT [kg]	23
f_N [Hz]	50 60	LIQUID CAP. [kg]	8,1
I_N [A]	1,9 2,3	STANDARD	IEC 60871-1/05
BIL [kV]	LIVE CASE !	INT. FUSES	NO
TEMP. CAT.	-40/C	SIDE BRACKETS	YES
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES
DISCHARGE	75 V/600 s (120 MΩ)		

DRAWING No.:	4K0745A	TYPE:	PUFFS 23-24/0,25
--------------	---------	-------	------------------



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
Pod černým lesem 683
564 01 Žamberk
Czech Republic

tel.: +420 465 673 111
fax.: +420 465 612 319
e-mail: zez@zez-silko.cz
http:// www.zez-silko.cz