



Total creepage [mm]	435
Air-distance [mm]	210
Dry-flashover [kV]	110
Wet-flashover [kV]	70
Drywithstand [kV]	70
Wetwithstand [kV]	50
Impulse voltage [kV]	125

U_N [kV]	24	PARALLEL ELEM.	1	CONNECTION	I
Q_N [kvar]	(54,3 65,2)	SERIES GROUPS	14	CASE MATERIAL	Stainless steel
C_N [μ F]	0,30 (-5/+10%)	WEIGHT [kg]	25	DIMENSIONS:	
f_N [Hz]	50 60	LIQUID CAP. [kg]	8,4	A [mm]	145
I_N [A]	2,3 2,7	STANDARD	IEC 60871-1/05	B [mm]	330
BIL [kV]	LIVE CASE !	INT. FUSES	NO	C [mm]	644
TEMP. CAT.	-40/C	SIDE BRACKETS	YES	D [mm]	100
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES	DRAWN: Stehlík J.	
DISCHARGE	75 V/600 s (90 M Ω)			CHECKED: Prokopec M.	

DRAWING No.:	4K0746A	TYPE:	PUFFS 23-24/0,3	DATE:	14.4.2014
--------------	---------	-------	-----------------	-------	-----------

	ZEZ SILKO s.r.o. Žamberk CZECH REPUBLIC	ZEZ SILKO s.r.o. Pod černým lesem 683 564 01 Žamberk Czech Republic	tel.: +420 465 673 111 fax.: +420 465 612 319 e-mail: zez@zez-silko.cz http:// www.zez-silko.cz
--	--	--	--