



Total creepage [mm]	435
Air-distance [mm]	210
Dry-flashover [kV]	110
Wet-flashover [kV]	70
Drywithstand [kV]	70
Wetwithstand [kV]	50
Impulse voltage [kV]	125

U_N [kV]	24	PARALLEL ELEM.	2	CONNECTION	I
Q_N [kvar]	(90,5 108,6)	SERIES GROUPS	14	CASE MATERIAL	Stainless steel
C_N [μ F]	0,50 (-5/+10%)	WEIGHT [kg]	35	DIMENSIONS:	
f_N [Hz]	50 60	LIQUID CAP. [kg]	10,8	A [mm]	145
I_N [A]	3,8 4,5	STANDARD	IEC 60871-1/05	B [mm]	480
BIL [kV]	LIVE CASE !	INT. FUSES	NO	C [mm]	794
TEMP. CAT.	-40/C	SIDE BRACKETS	YES	D [mm]	100
LIQUID	M-DBT (NON PCB)	BOTTOM BRACKETS	YES		
DISCHARGE	75 V/600 s (90 M Ω)				

DRAWING No.:	4K0748A	TYPE:	PUFFS 23-24/0,5	DRAWN:	Stehlík J.
				CHECKED:	Prokopec M.
				DATE:	14.4.2014



ZEZ SILKO s.r.o.
Žamberk
CZECH REPUBLIC

ZEZ SILKO s.r.o.
 Pod černým lesem 683
 564 01 Žamberk
 Czech Republic

tel.: +420 465 673 111
 fax.: +420 465 612 319
 e-mail: zez@zez-silko.cz
 http:// www.zez-silko.cz